

Santoprene Safety Tubing Datasheet

Product Code: RCST

Product Description

Our santoprene tubing is a thermoplastic rubber product which offers excellent durability in a variety of applications. It offers superior resistance to wear as well as abrasion deterioration compared to tubing products.



Technical Specification

Properties	Values
Compound	Santoprene
Density (Specific Gravity)	0.97g/cm ³
Hardness (Shore A)	64°
Tensile Strength	7.1 MPa
Elongation at Break	440%
Minimum Temperature	-20°C
Maximum Temperature	135°C



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. RubberSmart cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

The smart way to buy rubber & plastics

Inner diameter (ID)	Outer diameter (OD)	Wall thickness	Length
1.6mm	4.8mm	1.6mm	15m
1.6mm	6.4mm	2.4mm	15m
3.2mm	6.4mm	1.6mm	15m
3.2mm	8mm	2.4mm	15m
4.8mm	8mm	1.6mm	15m
4.8mm	9.6mm	2.4mm	15m
6.4mm	9.6mm	1.6mm	15m
6.4mm	11.2mm	2.4mm	15m
8mm	11.2mm	1.6mm	15m
8mm	12.8mm	2.4mm	15m
9.6mm	14.4mm	2.4mm	15m
12.7mm	19.1mm	3.2mm	15m
19mm	28.6mm	4.8mm	15m



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. RubberSmart cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.